

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number  
**WO 2005/028119 A1**

(51) International Patent Classification<sup>7</sup>: **B05B 07/08**,  
B08B 03/02, F01D 25/00

[SE/SE]; Berghamnsvägen 61, S-165 71 Hässelby (SE).  
**HJERPE, Carl-Johan** [SE/SE]; Sigunvägen 4, S-131 46  
Nacka (SE).

(21) International Application Number:  
PCT/SE2004/001370

(74) Agent: **DR LUDWIG BRANN PATENTBYRÅ AB**; P.O.  
Box 17192, S-104 62 Stockholm (SE).

(22) International Filing Date:  
24 September 2004 (24.09.2004)

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0302550-9 25 September 2003 (25.09.2003) SE

(71) Applicant (*for all designated States except US*): **GAS  
TURBINE EFFICIENCY AB** [SE/SE]; P.O. Box 633,  
S-175 27 Järfälla (SE).


(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **ASPLUND, Peter**

[Continued on next page]

(54) Title: NOZZLE AND METHOD FOR WASHING GAS TURBINE COMPRESSORS



(57) Abstract: A nozzle (54) for cleaning a gas turbine unit (1) during operation. The invention further relates to a method for washing a gas turbine unit (1) during operation. The nozzle (54) is arranged to atomize a wash liquid in the air stream in an air intake (2) of the gas turbine unit (1) and comprises a nozzle body (40) comprising an intake end (41) for intake of said wash liquid and outlet end (55) for exit of said wash liquid. The nozzle further comprises a number of orifices (42, 46; 42, 46, 60) that are connected to the outlet end (55) and respective orifice (42, 46; 42, 46, 60) is arranged at a suitable distance from a centre axis (49) of said nozzle body (40), whereby the local density of the injected wash liquid in a desired area can be increased with preserved droplet size and thereby the efficiency of the cleaning process can be significantly improved at the same time as the risk for damaging the components in the gas turbine unit is significantly reduced.



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

— *with international search report*